

DECLARATION OF PERFORMANCE

No. 047

1. Unique identification code of the product-type: **D-3**
2. Intended use/es: **Prescribed general purpose masonry mortar (G) for external use in elements subject to non structural requirements.**
Acrylic adhesive for glassbricks.
3. Manufacturer: **DUROSTICK S.A., Paint, mortar & adhesive industry.**
Production factory: Patima Kororemi Aspropyrgos, Attica, PC.: 19300 Greece, www.durostick.gr
4. Authorised Representative:
5. System/s of AVCP: **System 4**
6. Harmonised standard: **EN 998-2:2016**
7. Declared performance/s:

Essential Characteristics	Performance
Reaction to fire	Class A1
Contents of chloride	$\leq 0.07 \%$
Water absorption	$\leq 0.3 \text{ kg/m}^2 \cdot \text{min}^{0.5}$
Water vapour permeability	$\mu 15/35$
Thermal conductivity ($\lambda_{10,\text{dry}}$)	0.82 W/m · K (tab. value)
Durability (against freeze-thaw)	NPD
Dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.


Signed for and on behalf of the manufacturer by:

Zoi Athanasiou - Head of Mortar Lab



Aspropyrgos 28.07.23

CE MARKING



DUROSTICK S.A.
ASPROPYRGOS-ATHENS PC: 19300
GREECE

12
DoP No. : 047

EN 998-2:2016

D-3

Prescribed general purpose masonry mortar (G) for external use in elements subject to structural requirements.
Acrylic adhesive for glassbricks

Proportion of constituents (by weight):

Cement: 20-30 %
Aggregates: 70-80 %
Additives: 0-4 %

Reaction to fire	Class A1
Contents of chloride	≤ 0.07 %
Water absorption	≤ 0.3 kg/m ² · min ^{0,5}
Water vapour permeability	μ 15/35
Thermal conductivity ($\lambda_{10,dry}$)	0.82 W/m · K (tab. value)
Durability (against freeze-thaw)	NPD
Dangerous substances	See SDS