

DECLARATION OF PERFORMANCE

No. 081

1. Unique identification code of the product-type: **VINYL 300**
2. Intended use/es: **Improved cementitious adhesive with reduced slip and extended open time**
3. Manufacturer: **DUROSTICK S.A., Paint, mortar & adhesive industry.**
Production factory: **Patima Kororemi Aspropyrgos, Attica, PC.: 19300 Greece, www.durostick.gr**
4. Authorised Representative:
5. System/s of AVCP: **System 3**
6. Harmonised standard: **EN12004:2007+A1:2012**
- Notified Body: **MIRTEC S.A. No. 0437**
ITC DIVIZE CSI No. 1390
7. Declared performance/s:

| Essential Characteristics | Performance |
|---|---------------------------|
| Reaction to fire | Class A1 |
| Bond strength as: Initial tensile adhesion strength | $\geq 1.0 \text{ N/mm}^2$ |
| Durability for: Tensile adhesion strength after heat ageing | $\geq 1.0 \text{ N/mm}^2$ |
| Tensile adhesion strength after water immersion | $\geq 1.0 \text{ N/mm}^2$ |
| Tensile adhesion strength after freeze-thaw cycles | $\geq 1.0 \text{ N/mm}^2$ |
| Release of dangerous substances | See SDS |


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
Zoi Athanasiou - Head of Mortar Lab



Aspropyrgos 28.07.2023

CE MARKING



DUROSTICK S.A.
ASPROPYRGOS-ATHENS PC: 19300
GREECE

07
DoP No. : 081

EN12004:2007+A1:2012

VINYL 300

Improved cementitious adhesive with reduced slip and extended open time,
for internal and external tiling

| | |
|---|---------------------------|
| Reaction to fire | Class A1 |
| Release of dangerous substances | See SDS |
| Bond strenght as: | |
| Initial tensile adhesion strength | $\geq 1.0 \text{ N/mm}^2$ |
| Durability for: | |
| Tensile adhesion strength after heat ageing | $\geq 1.0 \text{ N/mm}^2$ |
| Tensile adhesion strength after water immersion | $\geq 1.0 \text{ N/mm}^2$ |
| Tensile adhesion strength after freeze-thaw cycles | $\geq 1.0 \text{ N/mm}^2$ |