

DECLARATION OF PERFORMANCE

No. 084

1. Unique identification code of the product-type: **VINYL 100**
2. Intended use/es: **Normal setting cementitious adhesive, with reduced slip and extended open time**
3. Manufacturer: **DUROSTICK S.A., Paint, mortar & adhesive industry.**
Production factory: **Patima Kororemi Aspropyrgos, Attica, PC.: 19300 Greece, www.durostick.gr**
4. Authorised Representative:
5. System/s of AVCP: **System 3**
6. Harmonised standard: **EN12004:2007+A1:2012**
- Notified Body: **MIRTEC S.A. No. 0437**

7. Declared performance/s:

Essential Characteristics	Performance
Reaction to fire	Class A1
Bond strength as: Initial tensile adhesion strength	$\geq 0.5 \text{ N/mm}^2$
Durability for: Tensile adhesion strength after heat ageing	$\geq 0.5 \text{ N/mm}^2$
Tensile adhesion strength after water immersion	$\geq 0.5 \text{ N/mm}^2$
Tensile adhesion strength after freeze-thaw cycles	$\geq 0.5 \text{ N/mm}^2$
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.


Signed for and on behalf of the manufacturer by:

Zoi Athanasiou - Head of Mortar Lab



Aspropyrgos 20.06.2023

CE MARKING



DUROSTICK S.A.
ASPROPYRGOS-ATHENS PC: 19300
GREECE

07
DoP No. : 084

EN12004:2007+A1:2012

VINYL 100

Normal setting cementitious adhesive with reduced slip and extended open time,
for internal and external tiling

Reaction to fire	Class A1
Release of dangerous substances	See SDS
Bond strenght as:	
Initial tensile adhesion strength	$\geq 0.5 \text{ N/mm}^2$
Durability for:	
Tensile adhesion strength after heat ageing	$\geq 0.5 \text{ N/mm}^2$
Tensile adhesion strength after water immersion	$\geq 0.5 \text{ N/mm}^2$
Tensile adhesion strength after freeze-thaw cycles	$\geq 0.5 \text{ N/mm}^2$