



## DECLARATION OF PERFORMANCE

No. 092

1. Unique identification code of the product-type: **EXTRA GOLD**
2. Intended use/es: **Improved deformable cementitious adhesive with reduced slip and extended open time**
3. Manufacturer: **DUROSTICK S.A., Paint, mortar & adhesive industry.**  
Production factory: **Patima Kororemi Aspropyrgos, Attica, PC.: 19300 Greece, www.durostick.gr**
4. Authorised Representative:
5. System/s of AVCP: **System 3**
6. Harmonised standard: **EN12004:2007+A1:2012**  
Notified Body: **ZÚS No. 1020**  
**ITC DIVIZE CSI No. 1390**
7. Declared performance/s:


Essential Characteristics	Performance
Reaction to fire	Class A1
<b>Bond strength as:</b> Initial tensile adhesion strength	$\geq 1.0 \text{ N/mm}^2$
<b>Durability for:</b> Tensile adhesion strength after heat ageing	$\geq 1.0 \text{ N/mm}^2$
Tensile adhesion strength after water immersion	$\geq 1.0 \text{ N/mm}^2$
Tensile adhesion strength after freeze-thaw cycles	$\geq 1.0 \text{ N/mm}^2$
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:  
**Zoi Athanasiou - Head of Mortar Lab**

Aspropyrgos 07.07.2023

CE MARKING



**DUROSTICK S.A.**  
ASPROPYRGOS-ATHENS PC: 19300  
GREECE

07  
DoP No. : 092

EN12004:2007+A1:2012

**EXTRA GOLD**

Improved deformable cementitious adhesive with reduced slip and extended open time,  
for internal and external tiling

<b>Reaction to fire</b>	Class A1
<b>Release of dangerous substances</b>	See SDS
<b>Bond strength as:</b>	
Initial tensile adhesion strength	$\geq 1.0 \text{ N/mm}^2$
<b>Durability for:</b>	
Tensile adhesion strength after heat ageing	$\geq 1.0 \text{ N/mm}^2$
Tensile adhesion strength after water immersion	$\geq 1.0 \text{ N/mm}^2$
Tensile adhesion strength after freeze-thaw cycles	$\geq 1.0 \text{ N/mm}^2$