

# DUROSTICK D-29 SPOT FREE



Oil repelling and waterproofing impregnating agent for tile & granite



## PROPERTIES

Siloxane based, oil repellent and waterproofing liquid, with high penetrating ability (micro technology). Once dry, the product creates an invisible and protective surface film, which does not peel and does not slip, even when the surface gets wet (increases the slip resistance of surfaces). Prevents stains from oils, wine and soft drinks, ink, as well as the creation of pet stains. Stains from mud rain and atmospheric pollutants are easily removed from surfaces protected with D-29 SPOT FREE.

## APPLICATIONS

DUROSTICK D-29 SPOT FREE is the necessary waterproofing agent for absorbent and/or non glazed tiles, matte and shiny granite, natural cotto, both indoors and out. Apply DUROSTICK D-29 SPOT FREE on kitchen countertops made of marble or granite, to keep them stain free. When installing absorbent tiles, granite and cotto, it is recommended to use the product before grouting with dark color

grouting materials. By so doing, the risk of the surface discoloration or staining, from the strong pigments of the grouting materials, is avoided and the cleaning process is facilitated at the same time.

## USE

### Surface preparation

Three weeks after completing the tile installation and the grout is thoroughly dry, clean all construction residues using DUROSTICK ACID TILE CLEANER. When dealing with existing tiles, refresh and clean the surface using the biodegradable cleaner for polished marble and granite, DUROSTICK BIOCLEAN.

### Application

Apply DUROSTICK D-29 SPOT FREE undiluted, using a paint roller or a brush, on dust free and dry surfaces. When dealing with an absorbent surface and the first coat is immediately absorbed, it is recommended to apply a second coat while the first one is still wet.

# DUROSTICK D-29 SPOT FREE



Oil repelling and waterproofing impregnating agent for tile & granite

**NOTE**

After drying, the product is harmless to health and the environment.

**COVERAGE**

100-150ml/m<sup>2</sup> per coat.

**CLEANING**

Clean all tools with DUROSTICK THINNER 101, immediately after use.

**STORAGE**

Store in shaded places away from any heat source, for at least 18 months from production date.

**SAFETY DIRECTIONS**

The product is classified as harmful. It is recommended to keep away from the reach of children and apply in well ventilated areas. Before use, refer to the cautions on the product packaging or the Material Safety Data Sheet.

**PACKAGING**

Carton box with 15 pcs. of 1lt each one  
Carton box with 6 pcs. of 4lt each one

TECHNICAL SPECIFICATIONS	
Form - Color	Liquid - Transparent
Density	0.77±0.04kg/lt
Gloss	Matte
Application temperature	From +5°C to +35°C
Foot traffic	After 12 hours
Duration of watertightness	2 years (exterior waterproofing), 5 years (interior)
Water absorption coefficient	W≤0,5kg/m <sup>2</sup> ∕h
<b>V.O.C. (Volatile Organic Compounds):</b> Limit value of maximum VOC content according to EC (Directive 2004/42/EC) for the particular product (class A/h «Binding primers», Type SB): 750gr/lt (2010). Ready to use product contains maximum 672gr/lt V.O.C.	

**DUROSTICK S.A.**

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS  
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612

THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 10, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367

E-mail: info@durostick.co

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.