

D-15



Cesspool and sewer cleaner



■ PROPERTIES

Very powerful cleaner for cesspools and sewers.

Use it without dilution.

Deposits such as grease and soap scum lead to pipe scaling that results in clogging. The cleaner works on the pipe walls of the sewer system, dissolving all accumulations. D-15 cleaner is heavier than water and flows through it, easily reaching to where solidified fats and scum close the pores of the walls of the cesspool. It effectively breaks down the fats and scum, opening the pores of the walls.

The wastewater is now free to drain through the newly opened pores of the cesspool walls.

The avoidance of the cesspool overflow, the unpleasant odors and the necessity for frequent evacuations leads to savings.

■ ADVANTAGES

- Easy Application.
- Extremely efficient and affordable.
- Keeps the cesspools in proper operation (periodic use-maintenance).
- Cleanses and restores the porosity of cesspools.

■ APPLICATIONS

D-15 is used to clean sewer pipes and to open the pores of cesspool walls. Suitable for absorbent and septic tanks.

Empty it either into the piping system or directly into the tank.

■ USE

For cesspool cleaning, use 5kg per 8m³ of wastewater. After five days, the cleaner will open

D-15



Cesspool and sewer cleaner

the pores and the wastewater level will be reduced. Tanks or cesspools that have not been recently cleaned, may need a second application. For maintenance, empty 2kg of D-15 for every 8m³ of the cesspool, every six months. Clean the sewer system by emptying 2kg at the beginning of the network and repeating after 5 days.

■ CONSUMPTION

600-800gr/m³, depending on the use.

■ STORAGE

Store in shaded places away from any heat source, for 24 months from production date.

■ SAFETY DIRECTIONS

The product is classified as flammable and toxic. It is recommended to keep away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product packaging or the Safety Data Sheet.

■ PACKAGING

Carton box with 6 pcs of 5kg each one.

TECHNICAL SPECIFICATIONS	
■ Form - Color	Liquid - Transparent
■ Density	1.14±0.05kg/lit
■ Distinctive odor	Yes
■ Water soluble	No

Permit No. by General Chemical State Laboratory
ELEFSIS: 3093/2008

DUROSTICK S.A.,
MANUFACTURING OF ADHESIVES,
PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
Tel: +30 211 60 03 500-599, +30 210 55 16 500,
+30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
STREET, DA 10, GR: 570 22,
Tel: +30 2310 795 797, +30 2310 797 365,
Fax: +30 2310 797 367
Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.