

# DUROFLASH



**Cleaning-polishing emulsion for dashboards, consoles & leather or vinyl car seats**



## ■ PROPERTIES

A perfect combination of a mild detergent and a silicone-based water emulsion, enriched with lanolin wax. It yields a satin finish and it is solvent-free. It penetrates leather, rubber and vinyl pores, removing both all surface but also absorbed dirt. It delivers antistatic, long lasting protection. It minimizes the effects of solar radiation and humidity. It protects all the surfaces it is applied on from fading, discoloration, bursting, and slows down their eventual ageing.

## ■ APPLICATIONS

DUROFLASH is specially produced for the interior care of cars, dashboards and consoles as well as genuine leather or vinyl seats. Use it also on vinyl

roofs and door panels. It is indispensable for preserving all perimeter seals on doors, hoods as well as on exterior unpainted accessories from rubber or vinyl.

It is also highly effective for cleaning and maintaining leather or vinyl handbags and shoes.

## ■ USE

Shake the bottle well and spray the sections needed. With continuous movements and using a clean, dry, lint-free cloth, spread the product over those sections needed cleaning and restoration. It dries quickly; revitalizing the surface and making it look 'new'.

On surfaces where you want to avoid slipping, like the steering wheel or the seats, allow the material to act for about 10 minutes. Following,

# DUROFLASH



## Cleaning-polishing emulsion for dashboards, consoles & leather or vinyl car seats

rub the surfaces using a cloth to dry them off and the resulting surface will not slip.

### ■ STORAGE

Store in cool and shaded places, for 24 months from production date.

### ■ SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation.

However, it is recommended to keep away from the reach of children. If swallowed seek immediate medical advice and show the container or label.

### ■ PACKAGING

Carton box with 16 pcs of 300ml each one.

TECHNICAL SPECIFICATIONS	
■ Form - Color	Emulsion - White, becomes transparent when dry
■ Density	1.00±0.04kg/lt
■ pH	Neutral
■ Scent	Coconut
■ Contains	Aliphatic hydrocarbons 5% but less than 15%, non-ionic surfactants and cationic less than 5%

Permit No. by General Chemical State Laboratory  
ELEFSIS: 3093/2008

**DUROSTICK S.A.**,  
 MANUFACTURING OF ADHESIVES,  
 PAINTS & MORTARS  
**ATHENS:** ASPROPYRGOS, ATTICA, GR: 193 00,  
 Tel: +30 211 60 03 500-599, +30 210 55 16 500,  
 +30 210 55 98 350, Fax: +30 210 55 99 612  
**THESSALONIKI:** INDUSTRIAL PARK-SINDOS, S.B. 44,  
 STREET, DA 10, GR: 570 22,  
 Tel: +30 2310 795 797, +30 2310 797 365,  
 Fax: +30 2310 797 367  
 Email: [info@durostick.com](mailto:info@durostick.com)

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.