

# DUROSTICK DS-1090



Fiberglass mesh for plaster reinforcement with mesh size 10x10mm



## PROPERTIES-APPLICATIONS

Fiberglass mesh for plaster reinforcement. It has 10x10mm frame opening and weighs 110gr/m<sup>2</sup>. Distinguished for its resistance to alkaline environments. Its use results in significant reinforcement of the coating and prevents cracking resulting from expansions and contractions. Necessary for the reinforcement of plasters and thin floor screeds. Ideal for applications when plaster and cement screeds come in contact with different structure components, e.g. beams with bricks or bricks with columns. It is also suitable for the reinforcement of plaster in areas over electrical channels and conduits.

## PACKAGING

Roll of 1m x 50m on a 30 pcs pallet  
 Roll of 25cm x 50m on a 124 pcs pallet

TECHNICAL SPECIFICATIONS	
<b>Form</b>	Alkali resistant fiberglass mesh
<b>Color</b>	White or blue

## DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS  
 ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612  
 THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367  
 E-mail: [info@durostick.com](mailto:info@durostick.com)

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.