

DUROSTICK D-21



Cleaner for honed marble



PROPERTIES

Powerful cleaner for honed marble and mosaics. It easily removes stubborn stains, without leaving any marks, where common detergents fail.

APPLICATIONS

DUROSTICK D-21 permanently removes stains, created from the watering of plants, on balconies (pic 2), and spaces lined with white or colored honed marbles, both indoors and out. It removes stains from pets, air pollution and soot stains (pic.1), rust from the railings as well as oils, grease, ink, wine and soft drinks etc.

USE

Surface preparation

DUROSTICK D-21 is a very powerful cleaner. The use of protective eyewear and plastic gloves is highly recommended, during application. Before applying, it is recommended to test the cleaner on a blind spot of the marble, to avoid any possibility of corrosion or clouding that is very rarely observed in limited types of colored marble.

Application

Apply it undiluted to the surface, and lightly scrub using a sponge or a broom for up to a minute. When working with highly absorbent marble, repeat the process. Follow by rinsing with plenty of water, immediately after application. When used as part of the protective system for marble, after cleaning apply on the thoroughly dried surface, DUROSTICK D-22 (water and oil repellent) or NANO PROOF MARMO DS-275, thus avoiding the necessity of frequent cleaning. The application of DUROSTICK D-25, self polishing product for floors made of marble, honed granites and cotto, will restore their lost luster. Maintain that luster effect by periodically adding a minimal quantity of the polish into the mopping water.

CONSUMPTION

1lt/5-6m² of surface.

DUROSTICK D-21



Cleaner for honed marble

STORAGE

Store in shaded places protected from frost, for at least 36 months from production date.

SAFETY DIRECTIONS

The product is classified as corrosive. It is recommended to keep away from the reach of children and apply in well ventilated areas. Before use, refer to the cautions on the product packaging or the Material Safety Data Sheet.

PACKAGING

Carton box with 15 pcs. of 1lt each one 5lt, 20lt containers

TECHNICAL SPECIFICATIONS	
Form - Color	Liquid - Transparent
Density	1.05±0.05 kg/lt
pH	0-1
Application temperature	From +5°C to +35°C
Scent	Lemon
Flammable	No
Among others, it contains 10% phosphoric acid, citric acid and less than 5% non-ionic	

General Chemical State Laboratory Reg. No 5229/0/99. Permit No. General Chemical State Laboratory ELEFSIS 3093/2008.

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS
 ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612
 THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 10, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367
 E-mail: info@durostick.com

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.