

FAST CLEAN



Fireplace & barbeque cleaner



■ PROPERTIES

Powerful active cleaner. It removes stubborn stains of soot, coal, dry or burnt fat and melted wax, just by spraying, without the need to scrub the surfaces. It restores the lost luster of the surfaces on which it is applied.

■ ADVANTAGES

- Easy application.
- Effective with tough stains.
- Restores the original appearance and natural color of surfaces.

■ APPLICATIONS

DUROSTICK FAST CLEAN is ideal for both commercial and residential use on grills and barbeques, ovens

and fireplaces lined with fire bricks or cast iron. The use of FAST CLEAN is suitable for cleaning natural stones and fire bricks.

■ LIMITATION OF USE

Avoid the contact of the product or its vapours, with painted surfaces as well as ones made of aluminum, copper or brass as its powerful formula might damage those surfaces. Avoid cleaning artificial decorative stones.

■ USE

DUROSTICK QUICK CLEANER is a very powerful cleaning agent.

During application and rinsing, the use of protective plastic gloves, is recommended.

FAST CLEAN



Fireplace & barbecue cleaner

Spray from a distance of 20-25cm and allow for the product act for 5 minutes. Subsequently, rinse using a wet sponge and/or plenty of water.

On surfaces with persistent stains, repeat the process.

It is recommended to apply D-22, the water and oil repelling agent of D-22 after cleaning the decorative natural stones, around the hearth of the fireplace or barbecue, to protect against the absorption of grease and oil stains.

■ STORAGE

Store in shaded places, for 36 months from production date.

■ SAFETY DIRECTIONS

The product is classified as corrosive.

It is recommended to keep it locked, away from the reach of children and apply it in well ventilated areas.

Before use, refer to the cautions on the product packaging or the Safety Data Shee.

■ PACKAGING

Carton box with 18 pcs of 750ml each one, 5lt container.

TECHNICAL SPECIFICATIONS	
■ Form - Color	Corrosive liquid - Light yellow
■ Density	1.05±0.05kg/lt
■ Scent	Lemon
■ pH	12.5-13.5
■ Contains	Sodium hydroxide and between others, anionic, amphoteric surfactants less than 5% and phosphonates less than 5%

Permit No. by State Chem. ELEFSIS: 3093/2008

DUROSTICK S.A.,
 MANUFACTURING OF ADHESIVES,
 PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
 Tel: +30 211 60 03 500-599, +30 210 55 16 500,
 +30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
 STREET, DA 10, GR: 570 22,
 Tel: +30 2310 795 797, +30 2310 797 365,
 Fax: +30 2310 797 367
 Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.