

GREASE



Long lasting



■ PROPERTIES

Lithium grease for professional and residential use. It protects against rust and friction all moving metal parts in machinery and equipment. It maintains its fluidity over time and provides excellent lubrication that lasts.

■ ADVANTAGES

- High quality.
- High temperature resistance.
- Prevents wear from friction.

■ APPLICATIONS

DUROSTICK GREASE is suitable for the lubrication and protection of gears, battery terminals, cables, bearings, pumps, pistons, door and window hinges. Suitable for locks, chains, springs, sewing machines, sliding mechanisms, and other moving metal parts. It prevents odor leaks from metal or plastic manholes and floor drains.

■ USE

1. Surface preparation

Remove all rust and dirt from the application surfaces.

2. Application

Place the tip of the bottle at the application point and squeeze. For large surfaces, and by using a brush or a trowel, coat with the required amount of lubricant in order to protect the surfaces.

■ CONSUMPTION

Depending on the Application.

■ STORAGE

Store in shaded places away from any heat source, for 36 months from production date.

■ SAFETY DIRECTIONS

This product needs no hazard labeling under current European and National legislation.

GREASE



Long lasting

It is recommended though to keep away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

■ PACKAGING

Clear case with 10 vials of 125ml each one

Carton box with 12 pcs of 1lt each one.

TECHNICAL SPECIFICATIONS	
■ Form - Color	Viscous paste/liquid - Honey
■ Density	0.88±0.05 kg/lt
■ Drip point	>130°C

DUROSTICK S.A.,
MANUFACTURING OF ADHESIVES,
PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
Tel: +30 211 60 03 500-599, +30 210 55 16 500,
+30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
STREET, DA 10, GR: 570 22,
Tel: +30 2310 795 797, +30 2310 797 365,
Fax: +30 2310 797 367
Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.